



KEY FEATURES

Two Types Touch

Projected Capacitive Multi-touch / Resistive Touch

IP Rating

IP65 Front Panel

Support 3 Signal Interfaces

VGA/DVI/HDMI

Support Modular Extended Display

1 x HDBaseT / 2 x HDBaseT / Wifi Display

Various Mounting Type

VESA Mount 75 / Panel Mount

Advanced Voltage

Support USB Type C

SPECIFICATION

DISPLAY AND TOUCH SCREEN	Display	21.5" TFT LCD Monitor Projected Capacitive Multi-touch / Resistive Touch
	Max. Resolution	1920 x 1080
	Brightness	300 cd/m ²
	Contrast	5000 : 1
	Active Area	476.64mm x 268.11 (H x V)
	Response Time	25ms
	View Angle	178/178
	Backlight Lifetime	50,000 Hrs LED Backlight
BOTTOM I/O	USB	1 x USB port (touch to external PC)
	Display	1 x VGA 1 x DVI-D 1 x HDMI
	Audio	1 x Line-in
	External Display (opt.)	1 x HDBaseT 100M / 2 x HDBaseT 100M / Wifi Display
POWER	Type	20V USB Type C VDC Input / 12 to 24 VDC Input with DC Jack
ENVIRONMENT	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-20°C ~ 60°C
	Relative Humidity	80% RH@ 50°C, 300Hrs (non-condensing)
MECHANISM	IP Rating	IP65 Front Panel
	Construction	Aluminum Front Bezel
	Dimensions (W x H x D)	TBD
	Weight	TBD
OTHER	OSD Keypad	Multi-language OSD
	Speaker	2 x 3W

PACKING LIST

1 Monitor
1 Audio Cable
1 VGA Cable
1 USB Cable
1 Quick Guide