



Self-registration Kiosk

- IP65-certified water proof
- Wireless communication for data transition
- Long panel backlight lifetime

Touch Panel PC:
KS070-BT , KS101-BT , KS150-BT



KS070-BT



Ultrasound

- Compact size for portable solutions
- Superior 2D/3D graphics performance for high-quality medical imaging
- Abundant I/O interface to connect peripherals

System-On-Module:
AL9A3 , AL700



AL700



CT System

- Enhanced graphic decoding ability by rich expansion
- Real-time performance of image processing
- 4K Ultra-high display resolution

Motherboard:
KD331-C236 , KD330-Q170



KD331-C236



Medical PC

- Fanless design suitable for using in hospitals
- Powerful graphic computing capability
- Multiple display ports for diagnosing

Motherboard:
KU171/173 , SU251/253



KU171/173



Healthcare Information System

- Isolated I/O port for stable and safety output
- Compliant with medical regulations
- Easy clean and maintenance with antibacterial design

System:
MD711-SU



MD711-SU





Maintains Excellent Hygiene

Antibacterial finish



Performs Effortless Cleaning

Smooth Surface



Brings a Sense of Peace and Comfort

Fanless Construction



Easy and Safe Uses

Universal Design

Specification

Processor	6 th Gen Intel® Core™ Processor
Memory	2 DDR4 SODIMM up to 32GB
Rear I/O	2 GbE, 2 RS-232, 2 USB 2.0 (supports 4kV isolation) 4 USB 3.0 3 Wi-Fi Antenna Hole
Expansion	1 PCIe x16 Expansion Slot, 1 M.2
Display	1 DVI-I (DVI-D signal), 1 DP/HDMI
Certification	IEC 60601-1-2:2014 EN 60601-2:2015 ISO 14971:2007
Power	Wide Range 9-36V
Dimensions	182mm x 97.6mm x 200mm (W x H x D)

DFI Inc.

10F, No.97, Sec.1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22175, Taiwan
+886 (2) 2697-2986 | inquiry@dfi.com | www.dfi.com

