


## M.2-1PSE/2PSE



### Features

PORT	1 RJ45/2 RJ45
INTERFACE	PCIe x1
FORM FACTOR	M.2 B-M key 22mm x 42mm (0.87" x 1.65")

### Specifications

#### I/O CONNECTORS

- M.2-1PSE: 1 connector for 1 external LAN port
- M.2-2PSE: 2 connectors for 2 external LAN ports

#### POWER INPUT

- 9V-36V: 4-pin header (default), DC jack (opt.)

#### POWER OUTPUT

- Compliant IEEE 802.3af, up to 15.4W at 48V per PoE port

#### MOUNTING

- Terminal (Default)
- Bracket (Optional)

#### APPLIED MODELS

- All DFI systems and boards with M.2 interface.

#### TEMPERATURE

- Operating: 0°C to 70°C
- Storage: -40°C to 85°C


#### HUMIDITY

- 5% to 90%

#### DIMENSIONS

- M.2 B-M key 22mm x 42mm (0.87" x 1.65")

### Mechanical Drawing



### Ordering Information

Module Name	P/N	RJ45
M.2-1PSE	770-M21PS1-000G	1
M.2-2PSE	770-M22PS1-000G	2

### Packing List

1 M.2-PSE module	
1 M.2-LAN module	
1 cable (Length: 250mm)	A81-009348-016G

